

## CE declaration of Performance (DoP)

Issued in accordance with the construction products directive (CPD)

Nr; 19005

This is to certify that in compliance with the Council Directive 89/106/EEC of 21<sup>st</sup> December 1988 on construction products, as amended.

Decospan N.V., Lageweg 33, B-8930 Menen, Belgium  
Produced at same location.

Declares that the product detailed below conform to type as required by the above Directives as evidenced by the conformity Route below under attestation system 3 of Appendix ZA.2 of EN 14342 : 2013

Applied Harmonized Standards ; EN14342 : 2013 Wood Flooring

Characteristic	Standard	Performance declaration
Reaction to fire	Linked with the mean density EN 323/EN 672  Linked with the minimum overall thickness	Cfl-s1 >900 kg/m <sup>3</sup>  7.2 mm
Emission of formaldehyde	EN 717-1	E1
Content of PCP	CEN/TR 14823	< 5 ppm
Slipperiness	EN 1339 Annex J	Class ≥15 (USRV)
Thermal conductivity	EN 12667	0.14 W/mK
Biological durability	EN 335	Use Class 1

Notified Body: WOOD, Hof ter Vleest Dreef 3, B-1070 Brussels, Belgium  
Manufacturer's product : Decospan N.V.  
with specifications;

- 1203 x 190 x 7.2 mm
- HDF core with 2 sides of veneer
- Finished with ±70 g/m<sup>2</sup> UV- lacquer
- Pre-lacquered veneer wooden flooring
- Floating installation for indoor use

Standards applicables; EN 14342, EN 14354 (Wood veneer floor coverings)

Pieterjan Desmet  
C.E.O.

Date: 08/11/2019