








TECHNICAL DATA SHEET

PRODUCT SPECIFICATIONS			EN
Multi-Ply Oak wood flooring	EN 13489 (Free Class)	DOP PQ2022-7	
Dimensions	Plank	600-1900 x 190 x 14/3 mm	
	Box	8 planks / 2,888 m ² / 24.30 kg	
	Nested lengths	Max 2 per box (min 600 mm)	
	Pallet	40 boxes / 115.52 m ² / 990 kg	
Density	EN ISO 23996	+/- 600 kg/m ³	
Installation	ISO 24334	Drop Lock (floating or glued)	
Top Layer		3 mm European oak (Quercus Robur)	
Grading		Rustical (B+)	
Surface		Slightly brushed	
Bevel		4-sided bevel	
Finishing		Oxidative oil	
Gloss Level	60°	5-10 %	
Warranty conditions	Residential Use Commercial Use	20 years upon request	
Application	EN 13489	Class 23 – Heavy residential use	

PRODUCT PROPERTIES			
PROPERTY	TEST METHOD	MIN. REQ.	RESULT
Indoor air certifications			A, REACH
SVHC screening (REACH / ECHA)	GZTC CHEM-TOP-092	< 0.1%	OK
Fire resistance	 EN 13501-1		Dfl-s1 (CWFT)
Slip resistance (pendulum test)	 CEN/TS 15676		SRV 'dry' : 83 (parallel) SRV 'dry' : 90 (vertical)
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m ³	< detectable limit (E1)
Pentachlorophenol content	 EN 12673	< 5 ppm	< detectable limit
Underfloor heating	 EN 12667	R < 0.15 m ² K/W	R = 0.135 m ² K/W OK (max +28°C) + glued
Transit sound reduction	 EN ISO 10140		ΔLw 19 dB Underlay 'Moist & Sound' (floating installation)
Biological durability			Class 1

Cleaning and maintenance instructions see : www.lamett.eu

