

SPECIFICATIONS

Plank size	Length: 630-1860 mm Width: 190 mm Thickness: 15(3.5) mm
Box	Min 4 planks of 1.86 m 2.12 m ² 16 kg
Pallet	40 boxes
Structure	3-layer
Coating	Oxidative dried oil (Mont Blanc), UV oil (Natural, Pure), Hardwax oil (Paris Brown, Authentic Brown)
Texture	Slightly brushed
Standard colour	Natural Oil, Pure, Authentic Brown, Paris Brown, Mont Blanc and unfinished
Grading	Rustic AB
Top layer type	Dry sawn veneer
Top layer thickness	3.5 mm
Bevel	V-groove on the long side
Gloss	10 ± 5%
Locking system	Tongue and groove
Type of installation	Advised: glued

STRUCTURE



INSTALLATION



PRODUCT CHARACTERISTICS - General

Factor	Standard - EN 14342
Density	650 kg/m ³ , 15 mm
Reaction to fire	Dfl-S1
Formaldehyde emission	E1
PCP	≤ 5 ppm
Thermal conductivity	0.13 W/mK
Thermal resistance	0.12 m ² K/W
Biological durability	Class 1
Surface soundness	≥ 1.00 N/mm ²
Impact resistance	ECO
Moisture level	7% - ±2%
Floor heating	Allowed, according to specific standards