

TECHNICAL DATA SHEET

PRODUCT SPECIFICATIONS		EN
Multi-Ply Oak wood flooring	EN 13489 (Free Class)	DOP PQ2022-9
Dimensions	Plank	600-1900x150x10/3 mm
	Box	8 planks / 2.85 m ² / 20 kg
	Nested lengths	Max 2 per box (min 600 mm)
	Pallet	54 boxes / 153.90 m ² / 1100 kg
Density	EN ISO 23996	+/- 650 kg/m ³
Installation	ISO 24334	Tongue & Groove (glued)
Top Layer		3 mm European oak (Quercus Robur)
Grading		Rustical (AB+)
Surface		medium brushed
Bevel		4-sided bevel
Finishing		Matt lacquer (UV)
Gloss Level	60°	5-10 %
Warranty conditions	Residential Use Commercial Use	20 years upon request
Application	EN 13489	Class 23 – Heavy residential use



PRODUCT PROPERTIES			
PROPERTY	TEST METHOD	MIN. REQ.	RESULT
Indoor air certifications			A, REACH
Fire resistance	EN 13501-1		Dfl-s1 (CWFT)
Slip resistance	CEN/TS 15676:2007		USRV 70
Formaldehyde emission	EN 717-1	≤ 0.124 mg/m ³	E1
Pentachlorophenol content	EN 12673	< 5 ppm	< detectable limit
Underfloor heating	EN 12667	R < 0.15 m ² K/W	R = 0.06 m ² K/W OK (max +28°C)
Biological durability			Class 1

Cleaning and maintenance instructions see : www.lamett.eu

