

Paintable skirt

60 x 14 x 2400 mm ou 80 x 14 x 2400 mm

Lamett®

PASSION FOR FLOORS!

SPECIFICATIONS

Dimensions	Length: 2400 mm Height: 60 or 80 mm Thickness: 14 mm
Packaging	Per 5 pieces packed in shrinking foil
PEFC	according to the PEFC standard
Components	MDF with primingfoil (uv-lacquer)

MDF

Density	730 kg/m ³
Swelling	<12 (24%)
Tensile strength	> 0,55 (N/mm ²)

FOIL

this foil is recoatable with all popular lacquer systems

Components

Basic	melamine/urearesin-impregnated wood free paper with approx. 25% resin content
Paperweight	80gsm
Print	complete water based inks without any contingent of heavy metal
Surface	UV-hardened lacquer with a recoatable surface

End product

Final weight	approx. 85 gsm (using base paper with a grammage of 80 gsm)
Composition	45-60% base paper, 20-25% resin content and approx. 10% of lacquer

Advices for storage

Condition	original packaged (unopened)
Premises	dry, 13-22°C, 55-65% humidity
Period of storage	max. 9 months

Characteristics

Formaldehyde category	E1
Light fastness	WS6 - light blue
Scratch resistance	500g (Hoffman) or 3,0N (Erichsen)
Tape pulls	no effect with '3M 810' or 'Scapa 2901'
Surface tension	40mN/m