

# Cottage 260

01-06-2023

## technical data sheet






EN

### Grading description

Multi-Ply Oak wood flooring	EN 14342 (Free Class)	DOP PQ2021-2
Dimensions	Plank	600-2200 x 260 x 15/ 4 mm
	Box	6 planks / 3,432 m <sup>2</sup> / 25,00 kg
	Nested lengths	5 full planks
	Pallet	40 boxes / 137,28 m <sup>2</sup> / 1140 kg
Density	EN ISO 23996	+/- 650 kg/m <sup>3</sup>
Installation	ISO 24334	Drop Lock (floating or glued)
Top layer		4 mm European oak (Quercus Robur)
Grading		Rustic B
Surface		Slightly brushed
Bevel		Bevel 4V
Gloss level	60°	10 - 15 %
Finishing		Matt lacquer
Warranty conditions	Residential use	20 years
	Commercial use	upon request
Application	EN 14342	Class 31



### Product properties

Property	Test method	min. req.	result
Indoor air certifications			A, REACH
Fire resistance	 EN 13501-1		Dfl-S1
Slip resistance	 EN 13893		DS (≥ 0.30)
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m <sup>3</sup>	E1
Pentachlorofenol content	 EN 12673	< 5 ppm	< detectielimiet
Underfloor heating	 EN 12667	R < 0.15 m <sup>2</sup> K/W	R = 0,145 m <sup>2</sup> K/W OK (max +28°C) + glued
Biological durability			Class 1

Cleaning and maintenance instructions: [www.lamett.eu](http://www.lamett.eu)

