






technical data sheet

EN

Product specifications

Solid Oak wood flooring	EN 13489 (Free Class)	DOP MAS2021
Dimensions	Plank	600-1900 x 150 x 15 mm
	Box	6 planks / 1,71 m ² / 19 kg
	Nested lengths	min. 1
	Pallet	36 boxes / 61,56 m ² / 704 kg
Density	EN ISO 23996	+/- 650 kg/m ³
Installation	ISO 24334	T&G (glued)
Top layer		-
Grading		Rustic AB+
Surface		Slightly brushed
Bevel		Bevel 4V
Gloss level	60°	< 8%
Finishing		UV oil
Warranty conditions	Residential use	30 years
	Commercial use	upon request
Application	EN 13489	

Product properties

Property	Test method	min. req.	result
Indoor air certifications			A, REACH
Fire resistance	 EN 13501-1		Cfl-S1
Slip resistance	 EN 13893		DS (≥ 0.30)
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m ³	E1
Pentachlorofenol content	 EN 12673	< 5 ppm	< detectable limit
Underfloor heating	 EN 12667	R < 0.15 m ² K/W	R = 0,145 m ² K/W OK (max +28°C) + glued
Biological durability			Class 1

Cleaning and maintenance instructions: www.lamett.eu

